



TFP SUBSTRATE MAT 3MM 15M²

Accessories TFP heating cable mat

Art.no 1001149

GTIN 7071236000648

Underlay mat for TFP heating mat.

PRODUCT FEATURES

- Thickness 3mm.
- Density 60kg/m³.
- Compression
- Standard ISO 3386-1 100mm/min
- 10% - 0.01 N/mm²
- 20% - 0.02 N/mm²
- 25% - 0.02 N/mm²
- Reduces step noise. Step noise 17 - 19dB.
- Deformation temperature 100°C.
- Operating temperature -40°C - 95°C.
- Standards ISO 10140-8, SS 02 52 67, ISO 717-2
- 30% - 0.03 N/mm²
- 40% - 0.05 N/mm²
- 50% - 0.07 N/mm²
- 75% - 0.27 N/mm²
- Step sound
- Result ΔLw 17 - 19dB



PRODUCT DIMENSIONS

Product height/diameter	3mm	Product Width	1030mm
Product length	260mm	Product net weight	2600g

MAINTENANCE

Maintenance free

ADDITIONAL INFORMATION

Always follow the parquet supplier's installation instructions. Make sure that the parquet is suitable for underfloor heating, and if PE foil is required.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no

Thermo-Floor AS can not be held liable for any type of errors or omissions in our product information.

Product specifications may change without further notice.



**TFP substrate mat 3mm 15m² can be ordered from
www.thermo-floor.no/1001149**

All additional documentation are available on the above adress and on documents.thermo-floor.no/1001149

