







	Dancity (leg /m²)
	Density (kg/m³)

PRODUCT FEATURES

- Lower heating costs
- High compressive strength. Ideal for click laminate floors.
- Reduces step noise in the room and improves the acoustic properties.
- Good thermal insulation suitable for use on cold floors, e.g. in basements.

ADDITIONAL INFO	
Customs number	39211911

TFV UNDERLAG 6MM GRÅ 18M2 Art.no 5430450 GTIN 7071236012276

TFV underlay is used with TF heating foil.

HEATING CABLE SUBSTRATE DATA			
Density (kg/m³)	55		
Surface tension (millinewton/m - mN/m)	42		
Boards per carton (pcs)	36		
Footstep sound (Decibel) ISO 10140	23		
Pressure resistance (t/m²)	28		
Heating exchange level (W/mK)	0.0307		
Water absorption (vol%)	0.1%		
Board size (usable surface, aprox. nr. in m²)	0.5m ²		
Covered area per package (m²)	18m²		
Thermal resistance (m² K/W) (R-Value)	0.187m²·K/W		
Melting point	160°C		
Thermal decomposition	250°C		







PRODUCT DIMENSION	s			
Product height/diameter	10mm	Product Width	630mm	
Product length	810mm	Product net weight	6850g	

MAINTENANCE

Maintenance-free

ADDITIONAL INFORMATION

Always follow the floor manufacturer's installation instructions, and always check whether the floor is actually intended for underfloor heating.

Some floor types place special demands on the firmness of the underlying floor. In these cases, it may be necessary to put down a pressure distribution plate over the finished heating foil to meet the floor supplier's specifications.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no Heatit Controls AS can not be held liable for any type of errors or omittances in our product information. Product specifications may change without further notice.









TFV underlag 6mm GRÅ 18m2 can be ordered from www.thermo-floor.no/5430450

All additional documentation are available on the above adress and on documents.thermo-floor.no/5430450

