



TFV UNDERLAG 6MM GRÅ 39M2

EOL

Art.no 5430460

GTIN 7071236014614

TFV underlay is used with TF heating foil.

PRODUCT FEATURES

- Lower heating costs
- High compressive strength. Ideal for click laminate floors.
- Reduces step noise in the room and improves the acoustic properties.
- Good thermal insulation - suitable for use on cold floors, e.g. in basements.

HEATING CABLE SUBSTRATE DATA

Density (kg/m ³)	55
Surface tension (millinewton/m - mN/m)	42
Boards per carton (pcs)	60
Footstep sound (Decibel) ISO 10140	23
Pressure resistance (t/m ²)	28
Heating exchange level (W/mK)	0.0307
Water absorption (vol%)	0.1%
Board size (usable surface, aprox. nr. in m ²)	0.65m ²
Covered area per package (m ²)	39m ²
Thermal resistance (m ² K/W) (R-Value)	0.187m ² ·K/W
Melting point	160°C
Thermal decomposition	250°C



MAINTENANCE

Maintenance-free

ADDITIONAL INFORMATION

Always follow the floor manufacturer's installation instructions, and always check whether the floor is actually intended for underfloor heating.

Some floor types place special demands on the firmness of the underlying floor. In these cases, it may be necessary to put down a pressure distribution plate over the finished heating foil to meet the floor supplier's specifications.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no
Thermo-Floor AS can not be held liable for any type of errors or omissions in our product information.
Product specifications may change without further notice.



**TFV underlag 6mm GRÅ 39m2 can be ordered from
www.thermo-floor.no/5430460**

All additional documentation are available on the above adress and on documents.thermo-floor.no/5430460

