







PRODUCT FEATURES

- Several other uses
- Very suitable for stabilizing pallets

D	D	$\boldsymbol{\cap}$	n		C.	т	n	Λ	т	Λ
Г	n	v	υ	U	L		v	M		M

Colour White

ADDITIONAL INFO

Customs number 35069100

TEC-BOND 410/43 10 KG

Hotmelt glue. Sold in packs of 10kg.

Art.no 8811367

GTIN 7071236004943

TF hot melt glue is a product consisting of 100% thermoplastic polymer. It contains neither water nor solvents, and is quickly melted with heat, allowing the glue to be applied in liquid form. TF hot melt glue is adapted to temperatures between 120°C and 215°C.

Hot melt glue is applied to the object you want to glue in a liquid/molten state. As soon as the parts to be glued are pressed together, the hot melt glue spreads outwards and into these parts. The glue then forms and cools down quickly, binding the parts together almost immediately.

Most materials can be glued together with hot melt glue, but only if the parts can be joined while the glue is still liquid. The opening time, ie. the time the glue stays liquid, varies from a few seconds to several minutes.









PRODUCT DIMENSIONS								
Product height/diameter	230.00000417233mm	Product Width	270.00001072884mm					
Product length	400.00000596046mm	Product net weight	10000g					

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no Heatit Controls AS can not be held liable for any type of errors or omittances in our product information. Product specifications may change without further notice.









TEC-BOND 410/43 10 kg can be ordered from www.thermo-floor.no/8811367



All additional documentation are available on the above adress and on documents.thermo-floor.no/8811367



